

AXIS Audio Manager Edge

Audio management for small and mid-sized systems

AXIS Audio Manager Edge is a free software application for managing up to 200 speakers in up to 20 zones. Embedded onboard Axis network speakers, it's suitable for small to medium sites including stores, factories, warehouses, and offices. It lets you set up your audio devices in separate zones where you can play various kinds of live or scheduled content – each from a single source. You can also easily set up weekly content schedules, and built-in health monitoring ensures you always know the status of your system.

- > **Built-in audio management system requiring no extra hardware**
- > **Manage up to 200 speakers and 20 zones**
- > **Mix live or pre-recorded announcements with ads and background music**
- > **Easy to schedule and set up weekly content**
- > **Know your system is working with built-in health monitoring**



AXIS Audio Manager Edge

Application		Network	
Compute platform	Edge. All Axis speakers have the capability to run AXIS Audio Manager Edge. In a system the leading speaker will run AXIS Audio Manager Edge.	Supported protocols	DHCP, DNS, IPv4, HTTP, HTTPS, mDNS, MQTT, IGMP, NTP, RTP, RTSP, SIP, TCP, TLS, UDP
Supported devices	AXIS C1004-E, AXIS C2005, AXIS C3003-E, AXIS C8033, AXIS C8210, AXIS C1310-E, AXIS C1410	Security	Media and communication encryption between devices. Proxy with optional authentication. Web stream authentication.
Licenses	No license needed.	System integration	
Settings	Volume control and calibration on site, zone and device level. Scheduling and management of audio content. Paging by SIP, VAPIX Audio and VAPIX Media Clip. Configurable User Management.	Audio streaming	Support for HTTP and HTTPS web stream formats: M3U, PLS Supported codecs: Mp3, MPEG, Ogg, Opus, WAVE
Configuration	Web configuration.	Audio files	Supported codecs: Mp3, MPEG, Ogg, Opus, WAVE
Scenarios		Audio sources	Compatible ACAPs, Line-in, local audio files, SIP (Mic and VoIP/PBX), VAPIX audio, VAPIX Media Clip, web streams. Two-way communication with SIP and VAPIX protocols. Echo/feedback loop elimination using half duplex mode.
Typical applications	Suitable for managing audio in commercial, educational, industry, and constitutional installations.	General	
Limitations	The application is limited to one site, 20 physical zones and 200 connected audio network devices. Limited to one background music content in all zones. Max audio file size to upload is 20 MB. The number of audio files that can be uploaded depends on the available memory in the device flash or SD card. Supports up to 200 streaming devices with multicast. Supports up to 20 streaming devices with unicast.	Languages	English, French, German, Italian, Dutch, Spanish

Environmental responsibility:

[axis.com/environmental-responsibility](https://www.axis.com/environmental-responsibility)